



by

**Shahzad Jamil**

**Forward Osmosis in Reverse Osmosis Concentrate  
Management**

**A thesis submitted in fulfilment of the requirements for the degree of  
Doctor of Philosophy**

Principal Supervisor  
Prof. Saravanamuthu Vigneswaran

**University of Technology Sydney  
School of Civil and Environmental Engineering  
Faculty of Engineering and Information Technology**

**JULY 2017**

# Certificate of Authorship

I certify that the work in this thesis has not previously been submitted for a degree nor has it been submitted as part of requirements for a degree except as fully acknowledged within the text.

I also certify that the thesis has been written by me. Any help that I have received in my research work and the preparation of the thesis itself has been acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

**Shahzad Jamil**

Production Note:

Signature of Student: Signature removed prior to publication.

Date: 08-11-2017

# Acknowledgement

First of all, I am very grateful to my supervisor Prof. S. Vigneswaran who has supported and guided me throughout my Doctor of Philosophy (PhD) study period. His encouragement has enabled me to develop solid back ground of the research topic.

I would like to thank Australian Postgraduate Award funded by the Australian Government, under the department of Innovation, Industry, Climate Change, Science, Research and Tertiary Education (DIICCSRTE), and a top up funded by University under the department of (DIICCSRTE).

I would like to extend my special thanks to my colleague Dr Sanghyun Jeong who fully supported me in my studies and guided me as a true friend.

I would also like to express my deep gratitude to other SCEE faculty members Dr. Hu Hao Ngo, Dr. Ho Kyong Shon Dr. Christian Kazner, A/Prof. Jaya Khandaswamy and Dr. Sherub Phuntsho for their support for my PhD studies.

Further I also acknowledge Mohammad Johir, Mr. David Hopper and Mr. Rami Hadad for their support in the laboratory work and equipment set up. I also acknowledge the administrative supports received from Phyllis Agius, Trish Dimasi, Craig Shuard, Tim Kevin, and Van Lee during this period.

Finally, I wish to thank my parents who, despite passed away, supported and motivated me in my studies. I would also like to thank my family for their support of my endeavours.

# Table of Contents

Certificate of Authorship .....	ii
Acknowledgement .....	iii
Abstract.....	xi
<b>Journal Articles Published</b> .....	xiv
<b>Conference papers and presentations</b> .....	xv
Nomenclature.....	xvi
<b>List of Symbols</b> .....	xviii
List of Figures.....	xx
List of Tables .....	xxiii
Chapter 1.....	1-1
INTRODUCTION .....	1-1
1.1 Background .....	1-2
1.2 Reverse osmosis .....	1-2
1.3 Reverse osmosis concentrate.....	1-2
1.4 Research motivation and significance.....	1-3
1.5 Research Objectives and Scope .....	1-6
1.6 The thesis is structured as follows: .....	1-9
Chapter 2.....	2-1
LITERATURE REVIEW .....	2-1
2.1 What is reverse osmosis concentrate (ROC).....	2-2
2.2 Treatment technologies for reverse osmosis concentrates .....	2-3
2.3 Principles of forward osmosis .....	2-6
2.4 Principles of pressure assisted forward osmosis .....	2-7

2.4.1	Pressure assisted FO for volume minimization reverse osmosis concentrates .....	2-10
2.5	Nano filtration and Reverse Osmosis.....	2-11
2.6	FO and PAFO performance parameters .....	2-15
2.6.1	Membrane performance .....	2-15
2.7	Performance and optimization of the forward osmosis process.....	2-18
2.7.1	Evaluation of draw solution.....	2-19
2.8	Membrane performance inhibitors .....	2-19
2.8.1	Membrane fouling.....	2-20
2.9	Concluding remarks .....	2-41
Chapter 3.....		3-1
MATERIALS AND METHODS.....		3-1
3.1	Introduction.....	3-2
3.2	Chemicals used.....	3-2
3.2.1	Draw solutions (DS) .....	3-2
3.2.2	Feed solution (FS).....	3-2
3.3	Experimental set-up .....	3-6
3.3.1	Forward osmosis unit.....	3-6
3.3.2	Forward osmosis membranes types .....	3-7
3.4	Experimental protocols .....	3-9
3.4.1	Performance measurements .....	3-9
3.4.2	Reverse solute flow.....	3-9

3.4.3	Salt rejection .....	3-9
3.4.4	Influence of membrane properties .....	3-10
3.4.5	Fouling experiments .....	3-11
3.4.6	Performance recovery .....	3-12
3.5	Analytical techniques .....	3-12
3.5.1	Conductivity, pH and temperature.....	3-12
3.5.2	Inductively coupled plasma emission spectrometry .....	3-12
3.5.3	Total organic carbon analysis .....	3-13
3.5.4	UVA measurement .....	3-14
3.5.5	Contact angle tests .....	3-14
3.5.6	Liquid chromatography-organic carbon detection.....	3-14
3.5.7	Micropollutants measurement and selected micropollutants.....	3-15
Chapter 4	.....	4-1
FO treatment of ROC from water reclamation plant	.....	4-1
4.1	Introduction .....	4-2
4.2	Experiment .....	4-3
4.2.1	Water and chemicals used.....	4-3
4.2.2	Analytical methods .....	4-5
4.2.3	Forward osmosis bench-scale unit.....	4-6
4.2.4	Experimental protocols .....	4-6
4.2.5	ROC volume reduction and rejection of organic micropollutants without GAC pretreatment using FO .....	4-7

4.2.6	Removal of TOC by fixed-bed GAC column.....	4-7
4.2.7	ROC volume reduction and rejection of organic micropollutants using FO after GAC pretreatment .....	4-7
4.3	Results and discussion.....	4-8
4.3.1	<i>FO without GAC pretreatment</i> .....	4-8
4.3.2	<i>FO with GAC pretreatment</i> .....	4-13
4.3.3	<i>Removal of organic micropollutants</i> .....	4-13
4.4	Conclusion.....	4-18
Chapter 5.....		5-1
Application of pressure assisted forward osmosis for water purification and reuse of reverse osmosis concentrate from a water reclamation plant .....		5-1
5.1	Introduction .....	5-2
5.2	Materials and methods .....	5-4
5.2.1	Reverse osmosis concentrate (ROC) .....	5-4
5.2.2	Chemicals and reagents .....	5-6
5.2.3	Bench-scale pressure assisted forward osmosis (PAFO).....	5-6
5.2.4	Experimental protocols .....	5-7
5.2.5	Fixed-bed GAC column.....	5-8
5.2.6	Analytical methods .....	5-8
5.3	Results and discussion.....	5-9
5.3.1	PAFO performance indicators .....	5-9
5.3.2	Fluxes with different applied pressures with ROC.....	5-12
5.3.3	Fouling and its mitigation .....	5-14

5.3.4	Removed dissolved organic carbon fractions .....	5-22
5.3.5	Inorganic ion concentration .....	5-23
5.3.6	Removal of organic micropollutants.....	5-26
5.4	Conclusions .....	5-28
Chapter 6.....		6-1
Use of forward osmosis membrane at nanofiltration mode for reverse osmosis concentrate treatment .....		
6.1	Introduction .....	6-2
6.2	Materials and methods .....	6-4
6.2.1	ROC characteristics .....	6-4
6.2.2	Membranes used .....	6-6
6.2.3	Analytical techniques.....	6-8
6.2.4	Bench-scale Nanofiltration unit .....	6-8
6.2.5	TOC removal using fixed-bed GAC column.....	6-10
6.3	Results .....	6-10
6.3.1	Flux and fouling study with ROC with NF membrane.....	6-10
6.3.2	Flux and fouling study with ROC with FO membranes .....	6-12
6.3.3	Performance of FO membrane in NF operation ROC with pretreatment..... .....	6-15
6.4	Conclusion.....	6-18
Chapter 7.....		7-1
Membrane bioreactor as a pretreatment to Pressure assisted Forward osmosis hybrid system for water purification of synthetic reverse osmosis concentrate .....		
7.1	Introduction .....	7-2

7.2	Materials and methods .....	7-3
7.2.1	Synthetic Reverse osmosis concentrate (ROC) .....	7-3
7.2.2	Membrane Bioreactor Set-up.....	7-4
7.2.3	Experimental protocols .....	7-5
7.2.4	Analytical methods .....	7-6
7.2.5	Bench-scale forward osmosis unit .....	7-6
7.3	Results and Discussion.....	7-7
7.3.1	MBR pretreatment of Synthetic ROC.....	7-7
7.3.2	Effect on water flux in PAFO with applied pressure.....	7-9
7.3.3	Water flux with synthetic ROC in FO with and without MBR treatment .	7-10
7.3.4	Fouling recovery .....	7-12
7.3.5	Inorganic and organic fouling.....	7-14
7.4	Concluding remarks .....	7-18
Chapter 8.....		8-1
CONCLUSIONS AND RECOMMENDATIONS .....		8-1
8.1	Pretreatment of ROC .....	8-3
8.1.1	GAC pretreatment.....	8-3
8.1.2	MBR pretreatment .....	8-4
8.2	Main findings of FO and PAFO system.....	8-4
8.2.1	Flux performances .....	8-4
8.2.2	Use of final diluted DS .....	8-4

8.2.3	Reverse and forward solute performances.....	8-5
8.2.4	Concentration polarization.....	8-5
8.2.5	Membrane fouling and cleaning .....	8-6
8.3	Main findings of NF system.....	8-7
8.4	Recommendations for future study .....	8-9

# Abstract

The production of fresh water and the disposal of wastewater are the major challenges of the last few decades. Reverse osmosis (RO) membrane plants are used extensively for brackish water desalination and industrial water purification. These plants operate at about 75% product water recovery so that about 25% of feed water is wasted as concentrated brine. The large quantities of concentrated brine generated has a disposal problem especially when the plants are located inland. Because of high disposal costs there is need to re-use and conserve water. RO reject concentrate (brine) is being increasingly processed to recover additional potable water. In order to achieve higher recoveries, therefore, alternate processes are used. Out of them forward osmosis is attractive.

FO water desalination technique uses the natural osmotic pressure of the draw solute to drive osmosis rather than hydraulic pressure. Fertilizer drawn forward osmosis (FDFO) has been applied as a low cost water desalination option for agriculture purposes. This technique is further investigated by applying pressure on feed solution to enhance water permeate flux, which is called pressure assisted fertilizer drawn forward osmosis (PAFDO). PAFDO can enhance final dilution of the fertiliser draw solution beyond osmotic equilibrium concentration. In simple terms, this technique can be considered combination of FO and low pressure reverse osmosis RO. Due to the low cost desalination potential, the FO and PAFO processes have gained attention of the research community.

Reverse osmosis concentrate (ROC) produced in water reclamation and desalination plants can endanger the environment if it is not treated before discharge. Volume minimisation of ROC can help in its easy disposal. The study examined the use of

forward osmosis (FO and PAFO) with and without granular activated carbon (GAC) fixed bed adsorption pretreatment for volume minimisation of ROC and removal of organic micropollutants.

In this study FO and PAFO were assessed in treating reverse osmosis concentrate using a low concentration of (KCl) as fertiliser DS. A low concentration of KCl (0.25 M) was chosen as DS and it was diluted to 0.14 M KCl during the FO operation due to transport of water permeate flux from feed solution. This diluted KCl solution can be used for direct fertigation, as the past studies showed successful use of 10 Kg/m<sup>3</sup> ( $\approx$ 0.13 M KCl) for fertigation.

Forward osmosis (FO) and nanofiltration (NF) membranes were tested to treat the ROC for possible water reuse. Due to very small pore sizes of FO membranes were used in nano-filtration mode to treat ROC from water reclamation plant. Commonly used NF membrane was good option for removing for organic compounds including micropollutants from wastewater however, most of inorganic compounds passed through the NF membrane. Since the FO membranes have pore size less than most of NF membranes, they also removed inorganic ions present in ROC. In this way the resultant permeate flux was able to be recycled back to RO unit to increase overall efficiency of the plant.

Fouling and scaling is an important and inevitable phenomenon in FO membranes as well. Lower membrane fouling and/scaling implies more product water, less cleaning and longer membrane life, thereby reducing operational and capital costs. It was observed that scaling and fouling were not fully reversed in FO/PAFO by physical cleaning. However, the physical cleaning followed by chemical cleaning could almost fully restore the activity of the membrane.

In this study, the membrane bioreactor (MBR) and granulated activated carbon were used as pretreatment methods to curtail organic fouling of the membrane. Both these pretreatment processes were proved to be successful to reduce total organic carbon of ROC including a majority of micropollutants. Moreover, inorganic carbon of ROC was reduced by acid pretreatment. These pretreatment processes resulted in high permeate water flux and less membrane fouling.

**Keywords:** Pressure assisted forward osmosis, Nano-filtration, chemical cleaning, membrane, Membrane bioreactor.

## Journal Articles Published

- 1) **Jamil, S.**, Jeong, S. & Vigneswaran, S. 2016, 'Application of pressure assisted forward osmosis for water purification and reuse of reverse osmosis concentrate from a water reclamation plant', *Separation and Purification Technology*, vol. 171, pp. 182-90.
- 2) **Jamil, S.**, Loganathan, P., Kazner, C. & Vigneswaran, S. 2015, 'Forward osmosis treatment for volume minimisation of reverse osmosis concentrate from a water reclamation plant and removal of organic micropollutants', *Desalination*, vol. 372, pp. 32-8.
- 3) Kazner, C., **Jamil, S.**, Phuntsho, S., Shon, H., Wintgens, T. & Vigneswaran, S. 2014, 'Forward osmosis for the treatment of reverse osmosis concentrate from water reclamation: process performance and fouling control', *Water Sci. Technol.* , vol. 69, no. 12, pp. 2431-7.

## Conference papers and presentations

1. **Jamil S.**, S.Jeong , and S. Vigneswaran Pressure Assisted Forward Osmosis for treating reverse osmosis concentrate from water reclamation plant, IWA World Water Congress & Exhibition 9-14 October 2016 Brisbane Australia.
2. **Shahzad Jamil**, P. Loganathan, S. Vigneswaran; Forward Osmosis and GAC adsorption hybrid system for RO concentrate volume minimisation and organic micropollutants removal, *Proceedings of the 9th IWA Micropol and Ecohazard Conference 22 - 25 November 2015, Singapore.*
3. **Shahzad Jamil**, C. Kazner, S. Vigneswaran Reverse osmosis concentrate treatment using forward osmosis for volume minimisation leading to zero liquid discharge *The 4th International Conference on Membrane Technology (3-6 Dec. 2014), HoChi Minh City Vietnam.*
4. **Shahzad Jamil**, Christian Kazner, Sherub Phuntsho, Hokyong Shon, Thomas Wintgens<sup>2</sup> and Saravanamuth Vigneswaran, Forward Osmosis for the Treatment of RO Concentrate from Water Reclamation: Process Performance and Fouling Control, 7th IWA Specialized Membrane Technology Conference · Toronto, Canada · 25 – 29 August 2013.
5. Kazner, C., **Jamil, S.**, Yapici, N., Fujioka, T., Listowski, A., Khan, S., Nghiem, L.D., Vigneswaran, S. & Wintgens, 'Behaviour of organic micropollutants in treatment of ROC from water reclamation towards zero liquid discharge', *Proceedings of the 8th IWA Micropol and Ecohazard Conference, EAWAG, Zurich, Switzerland*, pp. 114–5.

# Nomenclature

---

ICP	:	Internal concentration polarization
FDS	:	fertilizer draw solution
TOC	:	Total organic carbon
GAC	:	Granulated activated carbon
MDL	:	Method detection limit
OMs	:	Organic micropollutants
ROC	:	Reverse osmosis concentrate
TIC	:	Total inorganic carbon
$J_w$	:	water flux ( $L/m^2 h$ )
$P$	:	hydraulic pressure (bar)
$t$	:	membrane thickness ( $\mu m$ )
PAFO	:	Pressure assisted forward osmosis
PAFDO	:	pressure assisted fertilizer drawn forward osmosis
TDS	:	Total dissolved solids
MF	:	Microfiltration
UF	:	Ultrafiltration
NF	:	Nanofiltration
RO	:	Reverse osmosis
FO	:	Forward osmosis
FS	:	Feed solution
DS	:	Draw solution
AL	:	Active layer
SL	:	Support layer
MBR	:	Membrane biological reactor
CP	:	Concentration polarization
ECP	:	External concentration polarization
ICP	:	Internal concentration polarization
RSF	:	Reverse solute flux
AL-DS	:	Active layer – draw solution
AL-FS	:	Active layer - feed solution
DI	:	Deionized
MD	:	Membrane distillation
PSf	:	Polysulfone
PES	:	Polyethersulfone
PA	:	Polyamide
CTA-ES	:	Cellulose triacetate with embedded polyester screen
TFC-ES	:	Thin film composite with embedded polyester screen
PSF	:	Polysulphone
MWCO	:	Molecular weight cut-off
Norm.	:	Normalized
VMD	:	Vacuum Membrane Distillation
ZLD	:	Zero liquid discharge

---

BSA	:	Bovine serum albumin
HA	:	Humic acid
TOC	:	Total organic carbon
SEM	:	Scanning electron microscope
LMH	:	L/m <sup>2</sup> /h
HTI	:	Hydration Technology Innovations
DBPs	:	Disinfection By-Products
BTSE	:	Biological treated wastewater
WWTPs	:	Wastewater treatment plants

## List of Symbols

---

A	:	Water permeability coefficient ( $L \cdot m^{-2} \cdot h^{-1} \cdot bar^{-1}$ )
B	:	Salt permeability coefficient ( $m \cdot s^{-1}$ )
C	:	Solute number density ( $L^{-1}$ )
c	:	Solute concentration
D/Ds	:	Diffusion coefficient ( $m^2 \cdot s^{-1}$ )
Dh	:	Hydraulic diameter (m)
D	:	Salt diffusion coefficient
I	:	Intrinsic membrane structural properties
J <sub>s</sub>	:	Solute flux ( $g \cdot m^{-2} \cdot h^{-1}$ )
J <sub>w</sub>	:	Water flux ( $L \cdot m^{-2} \cdot h^{-1}$ )
J <sub>w, sp</sub>	:	Specific water flux ( $L \cdot m^{-2} \cdot h^{-1} \cdot bar^{-1}$ )
k	:	Mass transfer coefficient
M	:	Solute molar concentration ( $mol \cdot L^{-1}$ )
M	:	Molar concentration of the solution
Mw	:	Molecular weight ( $g \cdot mol^{-1}$ )
N	:	Moles of solute (mol)
n	:	Van't Hoff factor
P	:	Applied hydraulic pressure (bar)
Re	:	Reynolds number
Sc	:	Schmidt number
T	:	Absolute temperature (in K)
t	:	Thickness of the membrane (m)
Δt	:	Time interval (h)
ΔV	:	Volume change (L)
ΔP	:	Pressure change (bar)
Sh	:	Sherwood number
μ	:	Conductivity (mS/cm)
S	:	Structural parameter
σ	:	rejection coefficient
π	:	Osmotic pressure

---

## Superscripts/subscripts

w	:	Water
s	:	Solute
m	:	Membrane
i	:	Interface
D, b	:	Draw, bulk
F, b	:	Feed, bulk
F, m	:	Feed, membrane
D, m	:	Draw, membrane
W, sp	:	Water, specific

## Greek letters

$\pi$	:	Osmotic pressure (Pa)
$\varphi$	:	Osmotic pressure coefficient
$\sigma$	:	Reflection coefficient,
$\varepsilon$	:	membrane porosity
$\beta$	:	van't Hoff coefficient
$\tau$	:	pore tortuosity

# List of Figures

Fig.1. 1 Schematic of proposed integrated water reuse concepts for inland locations. .	1-6
Fig.1. 2 Structure of the thesis .....	1-9
Fig.2. 1 Application of FO in water, energy and life science fields (Zhao et al., 2012)	2-6
Fig.2.2 Forward osmosis for treating RO brine (Kazner et al., 2013; modified from Cath et al., 2006)	2-7
Fig.2.3 Flow diagram of an PAFO system	2-9
Fig.2. 4 (a) Concentrative internal CP and (b) dilutive internal CP across a composite or asymmetric membrane in FO (adapted from Cath et al., 2006)	2-18
Fig.2.5 Limiting factors for membrane desalination by reverse osmosis (adapted from Fritzmman et al., 2007)	2-20
Fig.2. 6 Treatment prior to membrane filtration [pre-treatment]	2-35
Fig.2.7 Treatment with membrane filtrations [integrated]	2-35
Fig.2. 8 Development of membrane hybrid systems (Ang et al. 2014; adapted from Shanmuganathan 2016).	2-36
Fig.3.1 Bench Scale FO set-up at the UTS laboratory.....	3-6
Fig.3.2 Overhead view of FO test cell with active flow cell of 2.6 x 7.7 x 0.3 cm on each side of the cell and double sealing.....	3-7
Fig. 4.1 Fixed-bed GAC adsorption column.....	4-8

Fig. 4.2. LC-OCD chromatogram of the initial and final FO feed solution after the first, fourth, and fifth step of the FO process without GAC pretreatment (LMW-low molecular weight, *concentration normalised to the initial volume). .....	4-10
Fig. 4. 3 Concentration of ions in initial feed solution (FO Step 1) and final feed solution (FO Step 5) after the final volume normalised to the original volume in FO without GAC pretreatment.....	4-11
Fig. 5.1 Water permeate flux ( $J_w$ ) profile at different applied pressures (0, 2, 3 and 4 bar) (Feed solution = DI water, and DS = 0.25 and 0.40 M KCl) .....	5-10
Fig. 5.2 Reverse solute flow with CTA-ES membrane using DI water as FS and 0.25 and 0.4 M KCl as DS. ....	5-12
Fig. 5.3 Water permeate flux ( $J_w$ ) profile at (0), 2, 3 and 4 bar applied pressures (FS = real ROC, and DS = 0.25 M KCl).....	5-13
Fig. 5.4 Comparison of flux in PAFO with and without pretreatment of ROC (Pressure = 3 bar, DS= 0.25 M KCl, and CTA-ES, HTI membrane in FO mode at 25 °C).....	5-15
Fig. 5.5 ROC fouled membrane recovery after DI water and acid flushing experiment (0.25 M KCl as DS and Pressure 3 bar at FS). ....	5-18
Fig. 5.6 Concentration of components in initial and final FS volume normalised to the original volume in PAFO with three different FSs: (A) ROC without any treatment; (B) ROC pH adjusted to 5; and (C) ROC - GAC pre-treated and adjusted pH 5. ....	5-25
Fig. 6.1 Schematic diagram of NF for ROC treatment with pretreatment.....	6-4
Fig. 6.2 Flow diagram of a bench-scale NF set-up used in this study. ....	6-9
Fig. 6.3 Water permeate flux ( $J_w$ ) profile of (a) NF030, (b) TFC-ES and (c) CTA- ES at 4 bar applied pressure (Feed solution = ROC from water reclamation plant). ....	6-14

Fig. 7. 1 Submerged MBR set-up .....	7-5
Fig. 7. 2 Mixed liquor suspended solids (MLSS) and mixed liquor volatile suspended solids (MLVSS). .....	7-8
Fig. 7. 3 Trans membrane pressure (TMP) with time; ( $J_w = 20 \text{ L/m}^2\cdot\text{h}$ ) .....	7-9
Fig. 7. 4 FO/PAFO flux with deionized water (DI) as feed solution at different applied pressures and 0.25 M KCl of draw solution .....	7-10
Fig. 7. 5 Comparison of flux and flux decline with and without MBR pretreatment at applied pressures (0, 3 & 4 bar and 0.25KCl as DS (TFC-ES membrane, $25^{\circ}\text{C}$ ). .....	7-11
Fig. 7. 6 Fouling recovery of TFC-ES membrane by flushing with DI water and acidic water of pH 4.5 (Water used for the experiments is DI water).....	7-14

# List of Tables

Table 2.1 : Overview of pressure-driven membrane processes and their characteristics - Van der Bruggen et al. (2003), (adapted from Shanmuganathan, 2015) .....	2-14
Table 2.2 General FO design criteria.....	2-18
Table 2. 3 Draw solutions .....	2-19
Table 2.4 Occurrence of pharmaceuticals in Australia (Pal et al. 2010) .....	2-25
Table 2. 5 Merits and demerits of different pretreatment processes used (adapted from Shanmuganathan, 2015).....	2-29
Table 3. 1 General composition of ROC .....	3-4
Table 3. 2 Chemical composition and properties of synthetic ROC .....	3-5
Table 3.3 Properties of the FO membranes used (references provided by the vendor, otherwise specified) .....	3-8
Table 3.4 Overview of selected and analysed trace organics .....	3-17
Table 4.1 Properties of the detected micropollutants and their initial concentration in ROC .....	4-4
Table 4.2 Volume reduction of ROC and flux decline during FO without GAC pretreatment .....	4-11
Table 4.3 Inorganic (I) and organic (O) carbon (C) adsorption on membrane during FO without GAC pretreatment (IC adsorbed at steps 4 and 5 cannot be calculated because part of the IC was lost to atmosphere as CO <sub>2</sub> ) .....	4-12
Table 4.4. Volume and flux decline during FO with GAC pretreatment .....	4-14

Table 4.5 Inorganic (I) and organic (O) carbon (C) adsorption on membrane during FO with GAC pre-treatment (IC adsorbed at steps 3, 4 and 5 cannot be calculated because part of the IC was lost to atmosphere as CO <sub>2</sub> ) .....	4-15
Table 4.6 Concentrations of organic micropollutants in initial ROC, in DS after Step 5 FO, in ROC after GAC treatment only and in DS after Step 5 FO with GAC pretreatment. ....	4-17
Table 5.1 Properties of the detected micropollutants in ROC and their initial concentration.....	5-5
Table 5.2 ROC volume reduction with PAFO at 3 bar pressure and 0.25M KCl as DS. ....	5-14
Table 5.3 Effectiveness of membrane cleaning with DI water wash and acidic water (pH 4.5) flushing after ROC fouling experiment (DS = 0.25 M; Pressure = 3bar; and Experiment duration = 16 h).....	5-17
Table 5.4 Total inorganic carbon (TIC) and total organic carbon (TOC) adsorbed on the membrane in PAFO: i) ROC without any treatment; ii) Softened ROC; and iii) Pre-treated ROC (by GAC and softening). (DS= 0.25 M KCl; applied pressure= 3 bar)..	5-21
Table 5.5 Organic fractions of ROC before and after GAC pretreatment (analysed by LC-OCD). ....	5-23
Table 5.6 Ionic species passed through the membrane from FS to DS. ....	5-24
Table 5.7 Concentrations of organic micropollutants in untreated ROC, in ROC after GAC treatment only, and in DS after GAC pretreatment and PAFO.....	5-27
Table 6.1 Characteristics of ROC .....	6-5
Table 6.2 Properties of NF and FO membranes (provided by vendor, otherwise specified).....	6-7

Table 6. 3 Rejection behaviour of NF and FO membranes with respect to ionic species present in ROC.....	6-11
Table 6.4 Behaviour of NF and FO membranes when ROC is used as FS. ....	6-12
Table 6.5 Behaviour of FO membrane (CTA-ES) in NF operation: i) ROC without any treatment; ii) ROC (GAC pretreatment) and iii) ROC ( GAC pretreated and softening) .....	6-16
Table 6.6 Rejection of inorganics by FO membrane (CTA-ES) in NF operation with GAC pretreatment and GAC along with acid pretreatment.....	6-17
Table7. 1 Water quality of Synthetic ROC.....	7-3
Table7. 2 LC-OCD analysis of Synthetic ROC and MBR treated ROC .....	7-7
Table7. 3 Inorganic scaling with synthetic ROC (FS), 0.25 M KCl (DS).....	7-16
Table7. 4 Inorganic scaling with MBR treated synthetic ROC (FS), 0.25 M KCl (DS).... .....	7-17