

# Sustainable Development & BIM – The Role of the 5D Quantity Surveyor

Dr. Peter Smith

*Associate Professor – University of Technology Sydney (UTS)  
Secretary General – International Cost Engineering Council (ICEC)  
peter.smith@uts.edu.au  
University of Technology Sydney  
PO Box 123, Broadway NSW 2007, Australia*

---

## ABSTRACT

BIM and its allied digital technologies provide enormous opportunities for project cost management professionals to dramatically improve the quality, speed, accuracy, value and sophistication of their cost management services. This is particularly the case during the design development stages when various design options are being proposed and evaluated. The ability of the quantity surveyor to use these digital technologies to provide quick and accurate cost advice throughout the design simulation process provides an enormous opportunity for the profession to play a key leading role in sustainable design development. BIM technologies facilitate the rapid simulation of a large number of sustainable design possibilities and the ability of the quantity surveyor to provide accurate and fast cost advice on these simulations is critical. The purpose of this paper is to explore the issues faced by firms in realizing these opportunities and to identify successful practices, procedures and strategies that firms are implementing. The research methodology for the paper is based on detailed interviews with Quantity Surveying firms and case studies of quantity surveying firms that are leading the way. The results show that there is a consistent pattern in relation to the main issues and problems and what was needed to be successful. The greatest issues related to the quality/comprehensiveness of the BIM models, difficulties with designers not providing full access to the models and software/standards compatibility issues. Successful strategies were clearly based on strong commitment and leadership from company directors and positive approaches to dealing with the issues and challenges faced.

**Keywords:** Existing Buildings, Retrofitting Business Case, Sustainable Retrofitting.

## INTRODUCTION

This paper explores the opportunities and practical issues and constraints faced by quantity surveying professionals in the implementation and effective utilization of the various software, technologies and tools that are now available in the Building Information Modeling (BIM) sphere with a particular focus on the important link between the utilization of these tools by quantity surveyors to provide critical cost services to the design and contracting project teams to optimise sustainable development and design project outcomes.

Building Information Modelling (BIM) provides both opportunities and challenges for the project cost management profession. As quantification increasingly becomes automated and BIM models develop the role of the project cost manager will need to adapt accordingly to provide more sophisticated cost management services that incorporate 4D time and 5D cost modelling and sharing cost information/data with the project team as part of the BIM integrated project delivery approach. The RICS (2014) contend that BIM provides project cost managers with the opportunity to spend more time on providing knowledge and expertise intensive advice to the project team - the automation of processes such as quantification will substantially reduce time spent on technical processes and will provide more time

and the digital tools for higher value-added and more sophisticated cost management services. Mitchell (2012) describes the importance for the project cost management professional to embrace the 5th dimension and become key players in the BIM environment – the ‘5D Project Cost Manager’.

However, the profession has generally been slow to embrace and evolve with the full potential that these technologies can provide. There is now considerable momentum building as firms realize they have to embrace these technologies and their competitors seize market advantage through developing expertise in the field. Momentum for change in the industry generally and via the use of digital technologies in particular has been slow but there has been a real acceleration for change across the globe in the past few years. It is important that quantity surveyors are not left behind. The World Economic Forum (2016) make the following comments that have been receiving global attention. *“While most other industries have undergone tremendous changes over the last few decades, and have reaped the benefits of process and product innovations, the Engineering & Construction sector has been hesitant about fully embracing the latest technological opportunities, and its labour productivity has stagnated accordingly. This unimpressive track record can be attributed to various internal and external challenges: the persistent fragmentation of the industry, inadequate collaboration with suppliers and contractors, the difficulties in recruiting a talented workforce, and insufficient knowledge transfer from project to project, to name just a few. The industry has vast potential, however, for improving productivity and efficiency, thanks to digitalization, innovative technologies and new construction techniques. Consider the rapid emergence of augmented reality, drones, 3D scanning and printing, Building Information Modelling (BIM), autonomous equipment and advanced building materials – all of them have now reached market maturity. By adopting and exploiting these innovations, companies will boost productivity, streamline their project management and procedures, and enhance quality and safety. To capture all this potential will require a committed and concerted effort by the industry across many aspects, from technology, operations and strategy to personnel and regulation”* (World Economic Forum 2016, p. 3).

## **5D BIM IMPLEMENTATION**

In line with these changes, the development of 5D (Cost) capabilities is gaining considerable momentum and leading edge project cost management firms are starting to realize the competitive advantages by embracing this ‘new-age’ approach to cost management. A major catalyst for the profession using this technology occurred in 2008 in the United States. The Association for the Advancement of Cost Engineering International (AACE), the American Society of Professional Estimators (ASPE), the United States Army Corps of Engineers, the General Services Administration (GSA) and the National Institute of Building Sciences (NIBS) formed an agreement to work together to solve cost engineering related problems for the facilities industry under the buildingSMART Alliance. The purpose was to develop systems and protocols for collaboration and coordination of cost engineering and estimating through the project lifecycle. *“The consortium continues to adjust to, and coordinate with ever-changing standards, so that the process of extracting and processing the 5D (cost) information from the BIM model is clearly defined, especially as the design evolves”* (ConstruchTech 2013, p.1).

In 2012 the Royal Institution of Chartered Surveyors (RICS) published new guidelines known as the Black Book (Quantity Surveyor and Construction Standards) and New Rules of Measurement (NRM). The Black Book is a comprehensive suite of documents that defines good technical standards for Quantity Surveying and Construction. The New Rules of Measurement suite provides a common measurement standard for cost comparison through the life cycle of cost management. *“The suite has been developed as a result of industry collaboration to ensure that at any point in a building’s life there will be a set of consistent rules for measuring and capturing cost data, thereby completing the cost management life cycle and supporting the procurement of construction projects from cradle to grave. A better understanding of costs during the construction process will increase certainty for business planning and support a reduction in spending on public and private sector construction projects in the long run”* (Property Wire 2012, p.1).

The New Rules of Measurement are integrally linked with BIM and enables a consistent approach to estimating and cost planning within BIM platforms. The RICS are currently looking at developing international standards in collaboration with other kindred associations and industry. The RICS have also recognized the need for global guidance for companies in terms of BIM implementation. They recently published a comprehensive ‘International BIM Implementation Guide’ for construction professionals and contractors that includes specific guidance for project cost managers (RICS 2014). They note that *“as the industry takes hold of this new future it is essential that organisations and individuals are not flying blind but have information to plot out a change plan and BIM implementation trajectory both for now and indeed a ‘future wise’ longer term digital strategy”* (RICS 04, p.1 )

The RICS (2015) have also recently developed a global 5D BIM implementation guide for cost managers. The guide focuses on the cost manager’s requirements from the BIM model to be able to effectively incorporate 5D BIM processes in project design and development. The main objectives of the guide are to: The main objectives of this guidance note are to: *“i. Assist the QS/cost manager in deriving benefits from delivering cost consultancy services in a BIM environment, by utilising model data rather than traditional manual measurement in the production of quantities, and ii) Inform the team in the needs of the QS/cost manager in performing their measurement role in a BIM environment* (RICS 2015, p.3).

The extent of firms effectively implementing 5D technology is difficult to gauge. An innovative project cost management firm in Australia provides a good example of what is starting to happen. Mitchell Brandtman are a medium sized quantity surveying firm in Australia that market their firm as ‘5D Quantity Surveyors and BIM Advocates and Specialists’. Their Managing Director, David Mitchell, contends that the modern day cost manager should be a 5D cost manager utilising electronic models to provide detailed 5D estimates and living cost plans in real time. Mitchell believes that the cost manager provides greatest value through their cost planning role at the conceptual front end stages of a project by providing cost advice and estimates on various design proposals and then refining those estimates as the design evolves. Using traditional 2D approaches this cost planning advice takes considerable time and inhibits rigorous comparative analysis within the allocated time frame for the design development process (Mitchell 2012).

Mitchell argues that the *“5D Cost Manager can do this extremely quickly, an endless number of times and in a complexity of combinations. A 5D Cost Manager can also re-estimate the developing design an endless number of times providing feedback on the estimate variances and corrective suggestions”* (Mitchell 2012, p.4). Mitchell (2012) refers to this as the 5D ‘Living Cost Plan’. He argues that these modern techniques can be used within traditional frameworks but that it is the behaviour and how the technology is used that is more important than the software.

## **5D BIM & SUSTAINABLE DEVELOPMENT**

5D BIM provides enormous opportunities for project cost management professionals to dramatically improve the quality, speed, accuracy, value and sophistication of their cost management services and therein ensure their future as key players in the BIM world. This is particularly the case during the design development stages when various design options are being proposed and evaluated. The ability of the quantity surveyor to use BIM models and other digital technologies to provide quick and accurate cost advice throughout the design simulation process will enable the profession to play a key leading role in sustainable design development. BIM technologies facilitate the rapid simulation of a large number of sustainable design possibilities and the ability of the quantity surveyor to provide accurate and fast cost advice on these simulations is critical.

Arnav (2015) contends that the greatest value of BIM lies in computer simulation that enables the project team to develop optimum design solutions for the project through the exploration of a number of design and construction options that are simply not feasible using conventional approaches.

BIM also enables the project team to simulate how the building will behave long before it is constructed – this has enormous benefits in developing sustainable development solutions as the long term operation of the building can be simulated many times. *“BIM has especially helped to enable sustainable design – allowing architects and engineers access to higher tech tools than ever before to carefully integrate and analyze things like heat gain, solar, ventilation, and energy efficiency in their designs”* (Arnav 2015, p.1)

He further highlights the importance of the economic (cost) analysis of sustainable design simulations and the ability to provide timely and accurate cost advice. *“The two most important considerations are the environmental and the economic impacts. While sustainability is important, it has to be feasible. Sustainable design is achieved only when it has a positive impact on both of these areas”* (Arnav 2015, p.1). Accordingly, the project cost manager/quantity surveyor has a key role to play in sustainable development by providing this economic analysis. Proficiency and expertise in 5D BIM is fundamental for the project cost manager/quantity surveyor to provide this analysis at the level required and which BIM technology now provides.

The 5D BIM project cost manager also has an important role to play in the measurement and costing of the operational and environmental performance of buildings. The Global Alliance for Buildings and Construction (GABC 2015, p. 8) note that *“Measurable, Reportable and Verifiable (MRV) information is pivotal to accelerating energy-efficiency in the buildings and construction sectors. In order to finance, construct, and renovate low-carbon, sustainable buildings, decision-makers in the building sector require high quality data to drive, motivate, finance, and require prudent policy action. At present, despite increasingly globalized building and construction markets, measurement and evaluation tools to track and monitor building performance, continue to vary considerably across the globe. However, it is important to calculate the energy savings’ multiple benefits, also towards the local market”*.

The lack of consistent measurable data provides opportunities for the project cost management profession to address this issue and become key players in the measurement and analysis of building operational performance. The GABC (2015, p. 8) stress that *“transparency and comparability rely on consistent data. Yet the way buildings are currently measured varies dramatically, this significant variability introduces high uncertainty in valuation and project-cost estimation”*. They highlight the need for the development of *“international standardized and vertically integrated (inter-governmental) measurement and reporting to enhance the understanding and international comparison of energy efficiency data and relevant resource flows for reduced GHG emissions”* and the *“development of international data, measurement, and standards”* in the built environment sector.

The project cost management profession is making the first steps towards addressing this issue through the development of ‘International Construction Measurement Standards’ (ICMS 2017). The development of an international construction measurement standard was initiated by the Royal Institution of Chartered Surveyors (RICS) and the European Council of Construction Economists (CEEC) in 2014. They were soon joined by the International Cost Engineering Council (ICEC) in support of the venture. Using their extensive international networks, these associations set about informing the project cost management profession about the initiative and inviting participation. The author was integrally involved and continues to be involved in this global industry consultation and development of the standard (ICMS 2017).

At the core of the development of the International Construction Measurement Standards (ICMS) is collaboration between the project cost management profession and their representative professional associations on a global scale. The ICMS coalition and support for the measurement standards has grown quickly. The coalition has now grown from a foundation membership base of 17 professional associations in mid-2015 to a membership of 41 associations by mid-2016. There are well over one hundred national associations as well as regional/international associations representing the profession around the world. The project cost management profession has traditionally been fragmented with a lack of global recognition – this is largely due to the different cost management approaches and various

cost management professional title descriptors used in various countries. This initiative is bringing the profession (be they quantity surveyors, cost engineers or other project cost management professionals) together to work on a global standard that has great potential to be recognised and endorsed by major global entities such as the World Bank, the International Monetary Fund and the United Nations as well as major multi-national corporations. These organisations are increasingly requiring global standards - gaining recognition and working with these types of organisations (and gaining their support) can provide the global platform for further standards to be developed, recognized and adopted around the world. The intention is for these international measurement standards to incorporate BIM measurement standards and, in time, environmental measurement standards. This presents tremendous opportunities for the profession to be key global players in the measurement and analysis of the environmental performance of buildings.

## **RESEARCH METHODOLOGY**

The research methodology adopted for this study was detailed industry interviews with medium to large quantity surveying firms in Australia. The quantity surveying firms interviewed comprised five firms (three medium sized firms with 20-30 employees and two large firms with 30 plus employees). The firms were located in NSW and Queensland. Four of the firms had experience with the use of BIM and automated quantities whilst the other firm, who primarily produces bills of quantities, interestingly had undertaken a considerable amount of research and trialling of BIM/automated quantities but has currently decided to remain using traditional approaches until the core issues surrounding the technology are addressed. This provided a good contrast to the other firms who are utilizing this technology. The interviewees were asked a range of questions relating to the issues, problems and benefits associated with the implementation of BIM and automated quantities. The following provides a summary of the main findings.

## **RESEARCH FINDINGS – INDUSTRY INTERVIEWS**

### **Collaboration With Designers & Development of Trust**

Architects, engineers and other design consultants are typically reluctant to provide full versions of their models to quantity surveyors, contractors and the like. There are a range of reasons with the main one being what will be done with the models and the potential liability of the designer. Many designers will only provide limited versions of their models to contractors and quantity surveyors for ‘information only’. Some cite intellectual property reasons but this flies in the face of the concept of BIM (sharing information as effectively and efficiently as possible) – the underlying reason is typically potential liability. A common thread from the interviewees was the importance of establishing strong collaborations with designers, gaining their trust over time and showing the value that that collaboration can provide for all parties. For example, as more detail is provided quantity surveyors have more scope to properly interrogate the model and identify errors/omissions/clashes which can be reported back to the designer for rectification. This has always been one of the traditional roles of the quantity surveyor in the 2D world and there is no fundamental difference in the BIM world. This collaboration should extend to explaining to designers the information/data that the quantity surveyor needs, in what form and how the model can be improved. It is important that the quantity surveyor can clearly articulate what they want and explain the benefits to the designer in providing such. Ideally the quantity surveyor needs the native files from the model. These requirements will change as the project evolves. For example, the information that the quantity surveyors requires from the model will vary considerably between the conceptual design stage, the cost planning stage, the detailed estimating/Bill of Quantities stage, the construction stage and the facility management stage of a project. One firm described their practice of a ‘brainstorming interrogation’ of BIM models for new projects. This may typically range from a few hours to a few days. They compile their team of experts to interrogate the model to identify issues, problems and information required. The results are then fed back to the designers/modelers for attention. The objective is to identify issues early and address them early.

## **BIM Data & Information**

To fully encapsulate the potential benefits of BIM models, the models need to be information rich with comprehensive and accurate data. This requires considerable time and expertise on the part of the BIM modelers and BIM team. On many projects the BIM model falls well short of its potential due to incomplete/inaccurate data. The reasons for this are numerous but the main reasons evolve around whether the design fees include allowance for the input of fully comprehensive data and whether the BIM team have the expertise/knowledge/information to input the necessary information into the model. Many clients do not see the value in paying the necessary fees for comprehensive models or may not have sufficient knowledge/advice to know whether this has been achieved. One quantity surveyor noted that he knew of an informal BIM forum for young BIM modelers sharing information on how to develop 'dumb' BIM models quickly that give the appearance that they are workable models and can quickly satisfy their clients' requirements. Then it will typically be the rest of the project team (contractors, subcontractors, quantity surveyors and the like) that need to work with the inadequate models and develop the further information required for construction.

## **Quantification**

Four of the firms interviewed used automated quantities software to prepare quantities on their projects – two firms used this software extensively particularly in the cost planning stages whilst the other two firms used such software in a limited capacity. The other firm, who primarily prepares Bills of Quantities at tender stage, rarely used automated quantities software as they felt that the quality and the accuracy of the BIM/3D models provided to contractors at tender stage was not sufficient to be able to rely on the quantities that may be automatically generated. The firms utilizing automated quantities used both proprietary and in-house software with the CostX program the most commonly used program. The CostX program is now the most widely used software of this type in Australia and is now used in over 40 countries around the world (Exactal 2017). The CostX program and the in-house programs were all capable of linking in with BIM models. The firms all agreed that they were on the 'automated quantities' path and that this would continue to develop as their own expertise and the software improved. The main issue that they found was in the quality of the electronic documentation (be it 2D, 3D or BIM models). The quality of documentation is critical to the development of accurate quantities and this issue has existed long before the introduction of electronic documentation. In the traditional 2D paper based days interrogation of the drawings and queries to correct design and information errors and inconsistencies was a normal part of the measurement process. The firms stressed that nothing has changed in the new electronic environment. The documentation still needs to be checked.

The new problem though is that it is more difficult to check the documentation accuracy despite advances in clash detection in BIM models. In the 2D days measurers would spend days and weeks measuring and 'absorbing' the project information in great detail. In the electronic 3D environment far less time is spent measuring and 'absorbing' and understanding the documentation details. There is also a new breed of young quantity surveyors who don't have that solid fundamental training in 2D paper-based measurement and may lack the experience and expertise to identify problems in CAD/BIM models as they might have done in the 2D environment. This leads to the major problem of not trusting the automatic quantities produced due to quality issues with the model. Problems may also occur where quantity surveyors are not fully conversant with the automated quantities software. This requires experience, expertise and intuition to be able to identify problems with the quantities produced. The firms only use automated quantities to the extent that is feasible – whilst ideally suited to cost planning measurement there are still limitations with more detailed measurement for Bills of Quantities, Builders Quantities and other detailed estimating requirements. Automatic quantities will also only reflect what is detailed in the model – the need to identify information and quantities not in the electronic model is critical. It is also of note that with all of the interviewed firms a considerable amount of measurement is still done via traditional means (i.e. not automated quantities) particularly with respect to detailed measurements for Bills of Quantities and Contract/Claims Administration. All firms saw automated quantities as a 'journey' as they evolve with the technology and use it where practical and useful.

## **Quantity Surveying BIM Analysis & Deliverables**

Mitchell (2013) contends that the 5D objective during design is to create a living cost plan that provides a transparent framework for making early cost decisions that have most impact on the final project outcomes. This is particularly the case with sustainable design simulations and proposals that have long term operational impacts. The living cost plan must be able to be revised and shared (on a weekly / fortnightly / or monthly cycle) using the current model information. The 5D objective during construction is to also provide a transparent framework for letting and administering construction contracts. The model map which created the cost plan becomes more detailed as the model Level of Development (LOD) progresses to become the basis for quantity take-off for letting and tendering, the valuation of variations, change orders and progress payments during construction and replacement work during operation of the building. The 5D objective on completion is to create a cost integrated 'as built' model that can be synchronised with the FM system to transfer replacement costs, base dates, expected and effective lives, estimated running and maintenance costs.

## **Clients**

All interviewees felt that there is a need for clients, both private sector and public sector, to drive the development of consistent modelling standards. The public sector has a key role to play to provide the necessary leadership for effective implementation. However, the interviewees consistently cited the lack of national government leadership in the field in Australia. Many felt that government were largely not interested and preferred to leave it to the private sector to move the industry forward. Some also cited the lack of expertise within government client bodies due to the now long-standing practice of outsourcing services to the private sector.

## **Education & Training**

Education and training requires substantial time and cost commitment from quantity surveying firms. Many interviewees identified the need for universities to help supplement this training so that graduates enter the industry with at least foundation knowledge in the BIM sphere and use of associated software and digital tools. The interviewees described a range of approaches to education and training in their workplace. One firm noted their practice of peer review at the end of each project. The work of the team on each project is reviewed by peers at the end of the project to identify BIM issues/problems, success factors, failure factors and lessons learnt. Most interviewees expressed concern about the issue of younger staff that may be proficient in the use of BIM models and associated software but lack fundamental knowledge and experience in the core competencies of the profession (construction/services technology knowledge, measurement principles and the like). Conversely, experienced older staff that struggle with this new technology. One firm cited their practice of teaming up younger/older staff members wherever possible so that they can work together and help overcome their respective deficiencies in knowledge/expertise and ultimately lead to long term continual improvement amongst their staff.

Certification was also raised. Certifications such as the 'Certified Practicing BIM Professional' will also help to develop professional understanding, skill and knowledge. This could involve certification of both individuals and companies. Examples cited included CanBIM from Canada. The CanBIM Certification Program for individuals is a tiered certification program providing a benchmark for individuals to be certified to nationally standardized and recognized levels of BIM Competency and Process Management (CanBim 2015).

## FUTURE STRATEGIES & DIRECTIONS

### Main Issues

The RICS (2014, p. 62) highlighted the following main issues facing project cost managers:

- QS professionals receive models developed by other project team members and are expected to perform their tasks using these models.
- Given that the models are developed by other project team members, the first important task that QSs have to undertake is to review the model for accuracy and information richness. Many instances have been reported where the model does not have the required information to allow model-based measurements and quantity take-off.
- It is important for the QS to ensure that the automatic model-based measurements and quantity take-off are compliant with locally accepted standard methods of measurements.
- Classification systems adopted by the project team may have an impact on the work processes of the QS. Commonly adopted classification systems are RICS' NRM, OmniClass Construction Classification System, ICE CESMM, MasterFormat, UniFormat and CPIC Uniclass.
- The LOD of the model must be clearly understood by the QS so as to ensure that cost planning is in accordance with the level of information that is available in the model.
- Models can change frequently in the BIM environment. This has both positive and negative connotations. QS professionals/firms are able to provide better cost planning information to clients due to the model-based measurement and quantity take-off. However, frequent changes may disrupt the workflow normally expected by QSs.

In addressing these issues the RICS (2014, p. 64) suggest that following broad structural changes may be needed: *“broader vision and behavioural changes from all stakeholders to collaborate on the BIM platform with a ‘whole of system’ and a ‘whole of industry’ approach; capacity building, education and training for BIM implementation; better value proposition for all stakeholders (including the articulation of the value proposition); development of national standards and guidelines; investment in research and development; participation of the academic community in updating curricula; process- and people-driven change and not technology-driven change; and a life cycle view for BIM implementation with strong integration with supply chain and asset management”*.

As outlined earlier in this paper, the RICS have recently developed a global guide ('BIM for Cost Managers: Requirements from the BIM model) to assist with this process. The global guide focuses on the development of standard protocols that can be adopted by quantity surveyors/cost managers. The RICS (2015) point out that *“the QS/cost manager needs to understand how a model, its attributes and other data will be created and conveyed at different stages of the project life. This will enable the QS/cost manager to make suitable adjustments to quantities, rates and other ancillary costs and modifications, at each work stage as appropriate. It is possible to link models to cost databases, and we expect this to evolve and develop in the future to provide a fully integrated BIM environment”* (RICS 2015, p. 5).

They then emphasise the need for the QS/Cost Manager to work with the design team to ensure that they get BIM information in the form that suits their processes. *“The different members of the design team may use different BIM authoring tools. Secondary tools may also be used for other purposes such as clash detection, data validation and 4D sequencing/programming (which can be used to review phasing – but this may be dependent on procurement route and contractor involvement). These should all be defined in the BIM Execution Plan (BEP). The exchange formats need to be agreed between the parties and the QS/cost manager (as a recipient of data) needs to state what formats and versions they require (such as IFC, DWF, DWFx, DWG, PDF)”* (RICS 2015, p.5).



## **BIM Modelling Standards for Measurement**

The variance in modelling standards remains a big issue for project cost managers. The lack of consistent modelling standards requires quantity surveyors to adapt to a range of approaches – this leads to obvious inefficiencies and wasted time. Project cost managers attempt to reduce this problem by developing collaborative relationships with designers as outlined earlier but this is a small piecemeal approach to an industry wide problem.

The development of national BIM modelling standards was viewed by interviewees as one of the most important factors in terms of successful long term BIM implementation. Ideally, the development of a global BIM Modelling Standard for Project Cost Managers/Quantity Surveyors would be the best approach. As outlined earlier, the International Cost Engineering Council (ICEC), the RICS, the European Council of Construction Economists (CEEC) and other professional associations are in the early stages of the development of a global International Construction Measurement Standard (ICMS). The purpose is to develop international standards through input and ownership by professional cost management associations around the world that are recognized by world bodies and national governments. There is much potential for this initiative to extend to the development of global BIM Measurement Standards and Environmental Measurement Standards. These global initiatives should have considerable influence on BIM software vendors and the industry generally. A few firms cited the UK BIM Standard 1192 (UniClass 1.4) as a good model that could form the basis of a global standard. Currently BIM software vendors largely determine modelling standards.

## **Level of Development (LOD) Specification Standards**

BIM specification standards during the various stages of development of a project are important for project cost managers and other construction professionals to assist them in defining their information requirements during these various stages. The BIM Forum (2013) have developed a Level of Development (LOD) Specification that has potential global application. It is a reference that enables professionals to specify and articulate with a high level of clarity the content and reliability of Building Information Models (BIMs) at various stages in the design and construction process. The LOD Specification utilizes the basic LOD definitions developed by the American Institute of Architects. It defines and illustrates characteristics of model elements of different building systems at different Levels of Development. This clear articulation allows model authors to define what their models can be relied on for, and allows downstream users to clearly understand the usability and the limitations of models they are receiving (BIM Forum 2013, p.8). The intent of this Specification is to help explain the LOD framework and standardize its use so that it becomes more useful as a communication tool. It does not prescribe what Levels of Development are to be reached at what point in a project but leaves the specification of the model progression to the user of this document. To accomplish the document's intent, its primary objectives are to help teams, including owners; to specify BIM deliverables and to get a clear picture of what will be included in a BIM deliverable; to help design managers explain to their teams the information and detail that needs to be provided at various points in the design process and to provide a standard that can be referenced by contracts and BIM execution plans. (BIM Forum 2013, p.8).

## **Modeling Existing Buildings**

New buildings only account for approximately 1 – 1.5% of the total building stock. Considerable work is being done on the modelling of existing buildings. This has important ramifications for the facility management and refurbishment/retrofit markets. Project cost managers need to get involved with this. The RICS (2014, p. 25) comment that 'with the proliferation of BIM there is now a need to capture as-built information, especially for large-scale retrofit and renewal projects. In these situations it is useful to start with the base digital model of the facility as it exists on site. This is now possible by linking laser scanning and 360-degree video or camera vector technology'.

## **Data Management**

The RICS (2014, p. 25) also contend that the large volumes of data that can be created in the BIM process need to be adequately managed. “To succeed in large-scale BIM projects, data management software should be used. Data management technology allows the modelling process to be connected with extended, dispersed and remote team members. Access control and security along with version control on the model and associated files is ensured through this technology”.

## **Evolving With Digital Technologies Generally**

Big Data is also an area that project cost managers should also embrace and evolve with. The ‘Internet of Things’ shows that in 5 years there will a 30 fold increase in devices connected to the internet. The future explosion in the number of intelligent devices will create a network rich with information that allows supply chains to assemble and communicate in new ways and will significantly alter supply chain leader information access and cyber-risk exposure (Gartner 2014). The information from these devices will be fundamental to Big Data and what can be done with this information. These transitions will affect how professionals behave in the future. Knowledge/possession of the data will have no value – the real value will lie on how this data is interrogated and interpreted.

Project cost managers are increasingly dealing with more connected, intelligent and demanding clients. The ‘Internet of Things, cloud computing, cloud-based collaboration, crowd sourcing, robotics, prefabrication, sustainability and the like are all areas that professionals in the industry need to evolve with and be part of.

## **CONCLUSION**

The full potential of BIM models is generally not being achieved. Objects in models commonly lack the substantive data that is required for project cost managers and other construction professionals to fully reap the benefits the model has the capacity to provide. This requires comprehensive and accurate data to be input by sufficient personnel with the necessary knowledge, experience and expertise and for adequate fees to be provided to ensure that this occurs. The key parties that need to invest in this data input are clients, developers and contractors. National and/or global object libraries and modelling standards also need to be developed to facilitate this. These remain big issues for the industry and impact directly on the ability of project cost managers to fully harness the potential of BIM.

The role of the 5D BIM project cost manager/quantity surveyor in the measurement and analysis of the economic impacts of various sustainable design and construction proposals put forward during the course of a project is very much dependent on the quality/comprehensiveness of the BIM model.

Ultimately, quantity surveying firms need to adopt proactive and innovative approaches that engage closely with the project design and construction teams to ensure that they get information from the BIM model in the forms that they require for their particular company processes and procedures. Rather than just accepting BIM information in the form that is just given to them at the whim of the design team, quantity surveying firms need to be able to clearly articulate their information requirements (and formats) and, perhaps most importantly, clearly demonstrate the value that this will provide for the design development and project success. This will typically also require the development of long term relationships between designers and contractors to foster levels of trust between the parties and the significant cost benefits that can be realised.

This has the very real potential to place quantity surveyors at the core of the design development process. Effective sustainable development and design relies on solutions that not only reduce environmental impact but can do so as economically as possible. Quantity surveyors should therefore be crucial to sustainable development via this economic input to the design team.

## REFERENCES

- Arnov, P. (2015), What is BIM and How Can It Lead To Sustainable Development? <https://indiansustainability.wordpress.com/2015/07/03/> (accessed 14 May 2017)
- BIM Forum (2013), Level of Development Specification, [www.bimforum.org/lod](http://www.bimforum.org/lod) (accessed 3 May 2017)
- ConstructTech (2013), Defining the 5D of Bim, [http://www.constructech.com/news/articles/article.aspx?article\\_id=9229](http://www.constructech.com/news/articles/article.aspx?article_id=9229) (accessed 25 June 2013)
- Exactal (2017), CostX, [www.exactal.com](http://www.exactal.com) (accessed 10 May 2017)
- Frei, M., Mbachu, J. & Phipps, R. (2013), Critical success factors, opportunities and threats of the cost management profession: the case of Australasian quantity surveying firms, *International Journal of Project Organisation and Management*, February 2013, Volume 5, Number 1
- GABC (2015), Global Alliance for Buildings and Construction Report, London, UK
- ICMS (2017), Internal Reports and Documents, International Construction Measurement Standards Coalition, <https://communities.rics.org/connect.ti/icmscoalition/view?objectId=14279365> (Viewed: 10 May 2017)
- Mitchell Brandtman (2013), 5D Cost Planning, <http://www.mitbrand.com>
- Mitchell, D. (2012), 5D – Creating Cost Certainty and Better Buildings, RICS Cobra Conference, Las Vegas
- Mitchell, D. (2013), 5D Quantity Surveyor – Here & Now, *JCT News*, pp 4-6, Thomson Reuters
- Muzvimwe, M. (2011), 5D BIM Explained, <http://www.fgould.com/uk/articles/5d-bim-explained/>
- Olatunji, O., Sher, W., Gu, N. (2010), Building information modeling and quantity surveying practice, *Emirates Journal for Engineering Research* Vol. 15, Issue 1, p. 67-70
- Property Wire 2012, p.1), RICS launches landmark new guidance to the construction sector, <http://www.propertywire.com/news/europe/rics-construction-industry-guidelines-201204246452.html> (accessed 5 April 2015)
- RICS (2014), International BIM Implementation Guide, 1st Ed, RICS Guidance Note, September 2014, Royal Institution of Chartered Surveyors, London, UK
- RICS (2015), BIM for Cost Managers: Requirements from the BIM Model, 1st Ed, RICS Guidance Note, August 2015, Royal Institution of Chartered Surveyors, London, UK
- Smith, P. (2015), Professional Standards For Quantity Surveying & Cost Engineering – Global Issues & Strategies, 19th Pacific Association of Quantity Surveyors (PAQS) Congress, June, Yokohama, Japan
- Wong, A., Wong, F. & Nadeem, A. (2009), Comparative Roles of Major Stakeholders for the Implementation of BIM in Various Countries, Hong Kong Polytechnic University
- World Economic Forum (2016), Shaping the Future of Construction - A Breakthrough in Mindset and Technology, World Economic Forum, Zurich, Switzerland