

Assessment of Residual Load Capacity of ASR Affected Reinforced Concrete Structures

by Jinsong Cao

Thesis submitted in fulfilment of the requirements for
the degree of

DOCTOR OF PHILOSOPHY

under the supervision of

Principal Supervisor: Dr Nadarajah Gowripalan

Co-Supervisor: A/Prof. Shami Nejadi

Co-Supervisor: Prof. Vute Sirivivatnanon

University of Technology Sydney
Faculty of Engineering and Information Technology

April 2021

Certificate of Original Authorship

I, *Jinsong Cao*, declare that this thesis, is submitted in fulfilment of the requirements for the award of Doctor of Philosophy, in the School of Civil and Environmental Engineering, Faculty of Engineering and Information Technology at the University of Technology Sydney.

This thesis is wholly my own work unless otherwise referenced or acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

This document has not been submitted for qualification at any other academic institution.

This research is supported by the Australian Government Research Training Program.

Signature:

Production Note:

Signature removed prior to publication.

Date: 12/04/2021

Acknowledgements

This PhD journey is like running a Marathon, it will not be possible without the support, training and patience provided by my supervisors, Dr Nadarajah Gowripalan, Dr. Shami Nejadi and Prof. Vute Sirivivatnanon. I feel so lucky to have all of you as my supervisors and I am grateful to you for providing me this precious opportunity to enrich the experience of my life, to broaden my horizon about my research, and more importantly, to see the big picture and overcome challenges during this journey. I am deeply grateful for your generosity, your invaluable guidance and continuous support.

I would also like to sincerely thank all staffs at UTS Tech Lab, especially Mr. Rami Haddad, Mr. Mulugheta Hailu, Ms Ann Yan and Mr. Peter Brown, Mr. Peter Winnacott, Mr. Scott Graham, the technical assistance, the facilities, equipment, and the team work you provided were really helpful for my experimental work.

Particularly, I would like to thank Dr Marie Joshua Tapas for generously providing support in performing SEM analysis and for confirming ASR products. Likewise, I would like to thank Ms Vu Tran Huyen and Mr. Thuc Nhu Nguyen for generously helping cast the three-meter long beams. I will never forget the scene when we were working together.

I am also thankful to all the friends I met. You are the ones that make my PhD journey full of laughter, happiness and beauty. I am the lucky one to see the spring, the summer, the autumn and the winter with you.

I am extremely grateful to my mother, for her love and encouragement.

I would like to thank the Australian Research Council Research Hub for Nanoscience Based Construction Materials Manufacturing (ARC NanoComm Hub) and Cement, Concrete & Aggregates Australia (CCAA) for providing financial support for the project.

List of Publications

- Cao, J., Gowripalan, N., Sirivivatnanon, V. & South, W. 2020, 'Accelerated test for assessing the potential risk of alkali-silica reaction in concrete using an autoclave', *Construction and Building Materials*, vol. 271, p. 121871.
- Gowripalan, N., Cao, J., Sirivivatnanon, V. & South, W., 2021, 'Comparison of the effect of ASR deterioration on the load carrying capacity of concrete structural elements in accelerated laboratory tests and in the field', Accepted for 16th International Conference on Alkali Aggregate Reaction in Concrete, June 2021, Lisbon, Portugal.
- Cao, J., Gowripalan, N., Sirivivatnanon, V. & South, W., 2019, 'Accelerated autoclave test for determining alkali silica reaction of concrete', *Concrete in Australia*, Vol. 45, No. 2, pp.37-40.
- Cao, J., Gowripalan, N., Sirivivatnanon, V. and South, W., 2019, 'Assessment of ASR expansions using an ultra-accelerated test', In 29th Biennial Conference of the Concrete Institute of Australia. Accepted for oral presentation in Concrete 2019 "Concrete in Practice-Progress Through Knowledge", September 8-11, 2019, Sydney, Australia.
- Gowripalan, N. and Cao, J., 2018, 'Effect of alkali silica reaction on bond strength and load capacity of reinforced concrete structures', *Proceedings of the 5th International fib Congress*, Melbourne, Australia, pp. 3088-3099.

Table of Contents

Certificate of Original Authorship	i
Acknowledgements	ii
List of Publications	iii
List of Figures	x
List of Tables	xvii
Abstract	xviii
Chapter 1	
Introduction	1
1.1 Background	1
1.2 Research Scope of the Whole Project.....	3
1.3 Research Objectives of the Current Project	3
1.4 Research Contributions.....	4
1.5 Structure of the Thesis	4
Chapter 2	
Literature Review	6
2.1 ASR Mechanism.....	6
2.2 Conditions for Deleterious ASR.....	9
2.3 ASR-Induced Concrete Expansion and Cracking	12
2.3.1 ASR Expansion	13
2.3.2 Cracking	19
2.4 Degradation of Mechanical Properties of ASR-Affected Concrete	22
2.5 Structural Effects of ASR.....	27
2.5.1 Bond Strength.....	27
2.5.2 Flexural Capacity.....	36
2.5.3 Shear Capacity.....	49

2.5.4	Long-term Behaviour.....	68
2.6	Secondary Effects of ASR - Corrosion of Reinforcement.....	71
2.7	Accelerated Test Methods for ASR.....	72
2.7.1	80 °C Accelerated Mortar Bar Test (AMBT)	72
2.7.2	38 °C Concrete Prism Test (CPT)	74
2.7.3	60 °C Accelerated Concrete Prism Test (ACPT).....	75
2.7.4	Ultra-accelerated Autoclave Test Methods for ASR.....	77
2.8	Numerical modelling of ASR.....	87

Chapter 3

Accelerated Autoclave Test for Assessing Alkali-Silica Reaction of Concrete		90
3.1	Overview	90
3.2	130 °C Autoclave Test Program.....	92
3.2.1	Materials and Mix Proportions.....	92
3.2.2	Specimen Fabrication and Autoclave Test Procedure	94
3.2.3	Expansion of Concrete Prisms	95
3.2.4	Testing of Mechanical Properties	98
3.3	Results and Discussion	101
3.3.1	Expansion and cracking of specimens	101
3.3.2	Compressive Strength Testing Results	103
3.3.3	Flexural Strength Testing Results	105
3.3.4	Modulus of Elasticity Test on 90-day Non-reactive Cylinders.....	106
3.3.5	Compressive Strength Test on 90-day Non-reactive Cylinders.....	107
3.3.6	SEM Observation of 90-day Non-reactive Cylinders after Autoclaving	108
3.4	Summary	110

Chapter 4

Novel Accelerated Test Method for ASR by Using an Autoclave		111
4.1	Overview	111

4.2	Phase I Experimental Program – Mortar Specimens	113
4.2.1	Materials and Mix Proportions.....	113
4.2.2	Specimen Fabrication and Steam Warming Procedure	115
4.2.3	Expansion Measurements	117
4.3	Results and Discussion for Phase I Experiments	118
4.3.1	Expansion of Mortar Bars	118
4.3.2	Influence of Total Alkali Content (2.5%, 3.0%, 3.5%)	119
4.3.3	Influence of Temperature on Expansion (70 °C and 80 °C).....	120
4.3.4	Microscopic Observation for Assessment of ASR.....	121
4.3.5	Summary of Phase I Experimental Program.....	125
4.4	Phase II Experimental Program – Concrete Specimens	126
4.4.1	Materials and Mix Proportions.....	126
4.4.2	Specimen Fabrication and Steam Warming Procedure	128
4.4.3	Expansion and Mass Change.....	131
4.4.4	Cracking of Specimens	134
4.4.5	Microscopic Observation	135
4.4.6	Mechanical Properties of Concrete under Accelerated ASR Test.....	138
4.5	Comparison of Expansion Results.....	141
4.5.1	Comparison of AMBT and 80 °C Autoclave Test Results	141
4.5.2	Comparison of CPT and 80 °C Autoclave Test Results	142
4.5.3	Summary	144
4.6	Concluding Remarks.....	144

Chapter 5

	Flexural and Shear Behaviour of Small-scale Reinforced Concrete Beams Affected by ASR.....	146
5.1	Overview	146
5.2	Experimental Program	149

5.2.1	Materials and Mix Proportions.....	149
5.2.2	Specimen Fabrication	150
5.2.3	ASR Acceleration.....	153
5.2.4	Expansion and Mass Change Measurements	154
5.2.5	Testing of Mechanical Properties	155
5.2.6	Load Capacity Test under Four-Point Loading.....	157
5.3	Results and Discussion	160
5.3.1	Cracking of Specimens	160
5.3.2	Length Change of Concrete Prisms	162
5.3.3	Modulus of Elasticity.....	163
5.3.4	Compressive Strength.....	164
5.3.5	Splitting Tensile Strength.....	165
5.3.6	Load Capacity of Reinforced Concrete Beams	166
5.5	Summary	181
 Chapter 6		
Bond Behaviour Between Reinforcing Steel Bar and ASR Affected Concrete.....		183
6.1	Overview	183
6.1.1	Effect of ASR on Bond Characteristics	183
6.1.2	Pull-out Test.....	187
6.1.3	Bond-slip Model (CEB-FIP Model Code 1990)	190
6.2	Experimental Program	192
6.2.1	Materials and Mix Proportions.....	192
6.2.2	Specimen Fabrication	193
6.2.3	ASR Acceleration.....	197
6.2.4	Testing of Mechanical Properties.....	198
6.2.5	Pull-out Test	198
6.2.6	SEM Examination for Steel-Concrete Interface.....	200

6.3	Results and Discussion	200
6.3.1	Mechanical properties.....	200
6.3.2	Bond Strength.....	201
6.3.3	Bond Stress - Slip Relationship.....	202
6.3.4	Microstructural Investigation	207
6.4	Summary	208
 Chapter 7		
Fabrication and Monitoring of Large-scale ASR-affected Beams		209
7.1	Overview	209
7.2	Specimen Fabrication and Conditioning.....	210
7.2.1	Specimen Design and Reinforcement Detailing	210
7.2.2	Materials and Mix Proportions.....	211
7.2.3	Concrete Mixing and Placement	213
7.2.4	Curing and Demolding of Beams	215
7.2.5	38 °C Climate Chamber Conditioning.....	218
7.3	Experimental Program	220
7.3.1	Expansion Measurements	220
7.3.2	ASR Acceleration.....	224
7.3.3	Testing of Mechanical Properties for Companion Cylinders.....	228
7.4	Results and Discussion	229
7.4.1	Match-cured Specimens.....	229
7.4.2	Visual Observations.....	234
7.4.3	Convex Curvature of Reinforced Concrete Beam Caused by ASR	248
7.4.4	Expansions	250
7.5	Summary	254
 Chapter 8		
Conclusions and Recommendations		257

8.1	Overview	257
8.2	Conclusions	258
8.3	Recommendations for Future Work	260
	References	262
	Appendices	280
	Appendix A. Morphology of ASR Products.....	280
	Appendix B. Mechanical Property Test Results (2.5% Na ₂ O _{eq} boosting)	291

List of Figures

Figure 2. 1 Alkali-silica reaction process (adapted from Giannini (2012)).....	6
Figure 2. 2 ASR expansion (Larive 1998)	16
Figure 2. 3 ASR induced expansion (Karthik, Mander & Hurlbaas 2016a)	18
Figure 2. 4 Macrocracking and microcracking due to ASR (Courtier 1990).....	19
Figure 2. 5 Cracking pattern of ASR affected reinforced concrete beam	21
Figure 2. 6 Experiment results of mechanical property degradation from literature.....	24
Figure 2. 7 Schematic diagram of stresses between ribs of a deformed reinforcement (Park & Paulay 1975).....	29
Figure 2. 8 Bond failure mechanism between ribs of deformed bar	30
Figure 2. 9 Schematic tensile stress ring in concrete (Tepfers 1979).....	30
Figure 2. 10 Bond behaviour at different ASR damage levels.....	35
Figure 2. 11 Flexural load capacity of reactive and non-reactive beams tested by.....	38
Figure 2. 12 Flexural load capacity of reactive and non-reactive beams tested by.....	42
Figure 2. 13 Flexural load capacity of reactive and non-reactive beams tested by Monette, Gardner & Grattan-Bellew (2002).....	45
Figure 2. 14 Moment capacity of reactive and non-reactive beams tested by	47
Figure 2. 15 Flexural capacity change with the expansion	48
Figure 2. 16 Reinforcement detail and shear span of tested beams	52
Figure 2. 17 Shear strength ratio (ASR damaged beam / control beam)	53
Figure 2. 18 Punching shear versus expansion of slabs (Clark & Ng, 1989).....	56
Figure 2. 19 Shear strength ratio (ASR damaged beam / control beam)	58
Figure 2. 20 Size of the specimen and schematic test set-up	63
Figure 2. 21 Fluorescent impregnated beam observed under UV light	63
Figure 2. 22 Shear test results vs. Calculated shear capacity	64
Figure 2. 23 Shear resistance change with restrained and free expansion	66
Figure 2. 24 Shear capacity of ASR affected concrete structures	68
Figure 2. 25 FE model of an ASR affected gravity dam.....	69
Figure 2. 26 Long-term deterioration of ASR affected dam	70
Figure 2. 27 Relation between expansion and total alkali content, different types of cement	79
Figure 2. 28 Effect of the water-to-cement ratio on the expansion of mortar bars	80
Figure 2. 29 Impact of autoclaving temperature on mortar bar expansions.....	81

Figure 2. 30 Impact of autoclaving duration on mortar bar expansions	82
Figure 2. 31 Laval/CANMET autoclave mortar bar test procedure	83
Figure 2. 32 Expansions of different mixtures under various alkali contents and autoclaving durations at 133 °C (Giannini & Folliard 2013).....	85
Figure 2. 33 Rheological model by Ulm et al. 2000.....	87
Figure 3. 1 Cracking of bridge beams due to ASR.....	90
Figure 3. 2 ASR affected bridge beams from a demolished bridge deck	91
Figure 3. 3 Test specimens in an autoclave.....	94
Figure 3. 4 Temperature-time and pressure-time relationships for one cycle of autoclaving	95
Figure 3. 5 Expansion of reactive aggregate B prisms with 3% Na ₂ O _{eq} boosting after autoclaving at ages of 3, 7, and 28 days.....	96
Figure 3. 6 Expansion of reactive aggregate B prisms with 5% Na ₂ O _{eq} boosting after autoclaving at ages of 3, 7, and 28 days.....	97
Figure 3. 7 Non-reactive concrete cylinders (90-day) in Zirbus LVSA 50/70 autoclave	101
Figure 3. 8 Average expansion (of 3 specimens made with aggregate B) at the ages of 3, 7 and 28 days	102
Figure 3. 9 Crack patterns of reactive aggregate B prisms with 3% Na ₂ O _{eq} boosting after 3 cycles of autoclaving at ages of 3, 7, and 28 days.....	103
Figure 3. 10 Compressive strength of 28-day value and.....	104
Figure 3. 11 Flexural strength of 28-day value and.....	105
Figure 3. 12 Residual modulus of elasticity compared to the 90-day value	107
Figure 3. 13 Compressive strength of non-reactive concrete cylinders tested at the age of 90 days and after 1, 2, 3 cycles of 130 °C autoclaving	107
Figure 3. 14 Microscopic observation on samples of autoclaved specimens by SEM .	109
Figure 4. 1 Grading curve of crushed aggregates.....	114
Figure 4. 2 Temperature and pressure in the autoclave chamber adopted for the multi-cycle accelerated test.....	117
Figure 4. 3 Expansion of specimens after steam warming in an autoclave	118
Figure 4. 4 Expansion – Alkali content relationship (80 °C autoclave steam warming)	119

Figure 4. 5 SEM-EDS map of ASR gel within an aggregate.....	122
Figure 4. 6 SEM-EDS map of ASR gel lining pore with sponge-like morphology	123
Figure 4. 7 SEM-EDS map of ASR gel at aggregate-cement paste interface	124
Figure 4. 8 Cumulated PSD of fine aggregates (Sydney sand)	126
Figure 4. 9 Cumulated PSD of coarse aggregates (dacite aggregate).....	127
Figure 4. 10 70L Pan mixer.....	129
Figure 4. 11 Zirbus LSVA 50/70 autoclave used for the test.....	130
Figure 4. 12 Specimens as placed in the autoclave	130
Figure 4. 13 Time-temperature cycles adopted in the autoclave chamber.....	131
Figure 4. 14 Expansion of concrete prisms after 3 cycles in the autoclave	132
Figure 4. 15 Mass change of concrete prisms after 3 cycles in the autoclave.....	133
Figure 4. 16 External cracks on cylinder after 3 cycles in the autoclave.....	134
Figure 4. 17 External map cracking on prism after 3 cycles in the autoclave.....	134
Figure 4. 18 Internal cracks and ASR gel in aggregate from concrete prism after 3 cycles in the autoclave observed using laser confocal scanning microscope	135
Figure 4. 19 SEM-EDS map of ASR gel formed in an aggregate.....	136
Figure 4. 20 SEM images showing ASR products with rosette-like morphology	137
Figure 4. 21 SEM images showing ASR products with network and plate-like morphology	137
Figure 4. 22 SEM images showing ASR products with crystalline morphology.....	138
Figure 4. 23 Influence of alkali loading on compressive strength of concrete cylinders tested at age of 3, 7 and 28 days	139
Figure 4. 24 Change in compressive strength and modulus of elasticity of concrete cylinders with 2.5% alkali boosting after 3 cycles in the autoclave.....	140
Figure 4. 25 Comparison of expansion results between 80°C autoclave treatment with alkali boosting and AMBT for dacite aggregate mortar bar	142
Figure 4. 26 Comparison of expansion results between 80°C autoclave treatment with 2.5% alkali boosting and CPT for dacite aggregate prism.....	143
Figure 5. 1 Detail of reinforcement of small-scale reinforced concrete beam.....	151
Figure 5. 2 Reinforcing steel bars in steel moulds.....	152
Figure 5. 3 Specimens cast for flexural and shear test.....	152
Figure 5. 4 Specimens as placed in the Zirbus LVSA 50/70 autoclave.....	154
Figure 5. 5 Length measurement using a comparator.....	155

Figure 5. 6 Modulus of elasticity test on 100 mm diameter 200 mm height cylinder ..	156
Figure 5. 7 Splitting tensile strength test.....	157
Figure 5. 8 Schematic test set up for load capacity test (adapted from ASTM C78) ...	158
Figure 5. 9 2D-DIC imaging systems	158
Figure 5. 10 Testing of reinforced concrete beams under four-point loading with 2D-DIC system.....	160
Figure 5. 11 Crack pattern of cylinders after 3 cycles of autoclaving	161
Figure 5. 12 External cracks on reinforced beam after 3 cycles in the autoclave	161
Figure 5. 13 White exudation on surface of small-scale reinforced concrete beam after 2 nd cycle of autoclaving	162
Figure 5. 14 Length change of concrete prisms after 3 cycles in the autoclave.....	163
Figure 5. 15 Change in modulus of elasticity of concrete cylinders	164
Figure 5. 16 Change in compressive strength of cylinders	165
Figure 5. 17 Change in splitting tensile strength.....	166
Figure 5. 18 Load capacity test results of small-scale reinforced concrete beam with two N5 deformed bars	167
Figure 5. 19 Beam D7-1: (a) Failure mode; (b) Load-displacement curve.....	169
Figure 5. 20 Beam D7-2: (a) Failure mode; (b) Load-displacement curve.....	170
Figure 5. 21 Beam D7-3: (a) Failure mode; (b) Load-displacement curve.....	171
Figure 5. 22 Beam D7-4: (a) Failure mode; (b) Load-displacement curve.....	172
Figure 5. 23 Beam D7-5: (a) Failure mode; (b) Load-displacement curve.....	173
Figure 5. 24 Load capacity test results of small-scale reinforced concrete beam with two N8 deformed bars	174
Figure 5. 25 Beam D4-1: (a) Failure mode; (b) Load-displacement curve.....	175
Figure 5. 26 Beam D4-2: (a) Failure mode; (b) Load-displacement curve.....	176
Figure 5. 27 Beam D4-3 after 1 cycle of autoclaving: (a) Failure mode; (b) Load-displacement curve	177
Figure 5. 28 Beam D4-4 after 2 cycles of autoclaving: (a) Failure mode; (b) Load-displacement curve	178
Figure 5. 29 Beam D4-5 after 3 cycles of autoclaving: (a) Failure mode; (b) Load-displacement curve	179
Figure 6. 1 Change in bond strength with expansion (Haddad & Nymayr 2007).....	185
Figure 6. 2 Change in bond strength with restrained expansion (Li et al. 2020)	186

Figure 6. 3 ASR gel formation at steel-concrete interface and its effect on bond (Gardoni et al. 2013).....	187
Figure 6. 4 Schematic pull-out test diagram (Castel & Foster 2015).....	188
Figure 6. 5 Influence of embedment length on bond stress distribution.....	190
Figure 6. 6 Bond stress – slip model (CEB-FIP Model Code 1990).....	190
Figure 6. 7 Rib pattern of 8 mm diameter deformed bar	193
Figure 6. 8 Pull-out test specimen design (50 mm bond length specimen)	194
Figure 6. 9 Reinforcing steel bars with 80 mm long tubes	195
Figure 6. 10 Rebars sitting in steel moulds ready for concrete casting	195
Figure 6. 11 Pull-out Specimens and cylinders + prisms.....	196
Figure 6. 12 Stress-strain curve of reinforcing steel bar	198
Figure 6. 13 Schematic diagram of pull-out test set up	199
Figure 6. 14 Instrumentation and test set-up for the pull-out tests.....	200
Figure 6. 15 Bond stress – slip relationship	203
Figure 6. 16 Bond stress – slip relationship and failure mode (specimens with 50 mm bond length, tested after 1 st cycle of autoclaving at 80 °C)	204
Figure 6. 17 Bond stress – slip relationship and failure mode (specimens with 50 mm bond length, tested after 2 nd cycle of autoclaving at 80 °C).....	205
Figure 6. 18 Bond stress – slip relationship and failure mode (specimens with 50 mm bond length, tested after 3 rd cycle of autoclaving at 80 °C).....	206
Figure 6. 19 SEM image of ASR gel with cracked platy-crystal morphology	207
Figure 7. 1 Reinforcement details of full-scale 3 m long reinforced concrete beam....	211
Figure 7. 2 Concrete mixing using a 70L pan mixer	213
Figure 7. 3 Slump test.....	214
Figure 7. 4 Concrete placement for plain concrete beam.....	214
Figure 7. 5 Concrete placement for reinforced concrete beam	215
Figure 7. 6 Moist curing of beams and companion specimens in the laboratory at a temperature of 23 ± 2 °C.....	216
Figure 7. 7 Demolding of R1 beam – reactive plain concrete beam	217
Figure 7. 8 Moving reinforced concrete beam into 38 °C climate chamber	219
Figure 7. 9 DEMEC points arrangement (R1 beam – reactive plain concrete beam) ..	221
Figure 7. 10 DEMEC points arrangement (R2 beam – reactive reinforced concrete beam)	222

Figure 7. 11 DEMEC points arrangement (R3 beam – reactive reinforced concrete beam)	222
Figure 7. 12 DEMEC points arrangement (R4 beam – reactive reinforced concrete beam)	223
Figure 7. 13 DEMEC points arrangement (NR1 beam, non-reactive reinforced concrete beam, flipped over)	223
Figure 7. 14 DEMEC points adhered on surface of cylinder and length measurement	224
Figure 7. 15 Water supplying conditions of plain concrete beam and reinforced concrete beams tested by Multon & Toutlemonde (2010)	225
Figure 7. 16 Schematic diagram of supplying water to the beams	226
Figure 7. 17 Water supply of R1 beam – plain concrete beam, simply supported	227
Figure 7. 18 Water supply of R3 beam – reinforced concrete beam	227
Figure 7. 19 Change in modulus of elasticity of cylinders with 1.25% alkali loading	230
Figure 7. 20 Change in compressive strength of cylinders with 1.25% alkali loading	232
Figure 7. 21 External cracks on cylinders after 1 year of immersing in water	234
Figure 7. 22 External cracks on cylinders at the age of 500 days, immersed in water and stored in 38 °C climate chamber, without autoclaving specimens	235
Figure 7. 23 External cracks on cylinders after 1 year of immersing in water and stored in 38 °C climate chamber (with 130 °C autoclaving for 5 hours at the age of 180-day)	236
Figure 7. 24 Comparison of cylinders at the age of more than 5 years cured in: (a) fog-room with 100%RH at 23 °C and (b) field exposure conditions (Karthik, Mander & Hurlebaus 2016b)	237
Figure 7. 25 External cracks on prism (after 500 days of immersing in water)	238
Figure 7. 26 R1 beam surface (photo taken on 03/05/2019 after the beam was moved into the 38 °C climate chamber)	239
Figure 7. 27 Cracking on R1 beam surface	240
Figure 7. 28 Cracking on R1 beam surface	240
Figure 7. 29 Map cracking on R1 beam surface	241
Figure 7. 30 Cracking on R1 beam surface	241
Figure 7. 31 Map cracking on R1 beam surface	242
Figure 7. 32 Cracking on R1 beam surface	242
Figure 7. 33 Longitudinal cracking on R2 beam surface	244

Figure 7. 34 Longitudinal cracking on R2 beam surface	245
Figure 7. 35 Longitudinal cracking on R3 beam surface	246
Figure 7. 36 Longitudinal cracking on R3 beam surface	247
Figure 7. 37 (a) Schematic set-up of laser displacement sensor; (b) Deployment of laser sensor for R2 beam to measure the displacement of the beam	249
Figure 7. 38 Upward displacement of R2 beam	250
Figure 7. 39 Average free expansion of prisms and cylinders stored in 38 °C climate chamber with the 3 m long beams	251
Figure 7. 40 Average longitudinal and lateral expansion of R1 plain concrete beam stored in 38 °C climate chamber	252
Figure 7. 41 Average longitudinal and lateral expansion of R2 reinforced concrete beam stored in 38 °C climate chamber.....	252
Figure 7. 42 Average longitudinal and lateral expansion of R3 reinforced concrete beam stored in 38 °C climate chamber.....	253
Figure A. 1 SEM images showing ASR products with rosette-type morphology.....	280
Figure A. 2 SEM images showing ASR products with rosette-type morphology.....	281
Figure A. 3 SEM images showing ASR products with crystalline morphology.....	282
Figure A. 4 SEM images showing ASR products with crystalline morphology.....	283
Figure A. 5 SEM images showing ASR products with rosette-type morphology.....	284
Figure A. 6 SEM images showing ASR products with rosette-type morphology.....	285
Figure A. 7 SEM images showing ASR products with crystalline morphology.....	286
Figure A. 8 SEM images showing ASR products with network and plate-like morphology (sample from 80 °C accelerated autoclave test)	287
Figure A. 9 SEM images showing ASR products with plate-like morphology	288
Figure A. 10 SEM images showing ASR products with plate-like morphology	289
Figure A. 11 SEM images showing ASR products with crystalline and rosette-type morphology (observed from 38 °C CPT test sample).....	290
Figure B. 1 MOE test results (28-day).....	292
Figure B. 2 MOE test results (after 1 cycle of 80 °C autoclaving).....	292
Figure B. 3 MOE test results (after 2 cycles of 80 °C autoclaving)	293
Figure B. 4 MOE test results (after 3 cycles of 80 °C autoclaving).....	293

List of Tables

Table 2. 1 Some potentially reactive aggregate types (Blight & Alexander 2011).....	11
Table 2. 2 Retained mechanical property in percentage of 28-day values of unaffected concrete (ISE 1992)	23
Table 2. 3 Shear capacity of slabs tested by Bilodeau et al. (2016)	61
Table 2. 4 Summary of ultra-accelerated autoclave tests.....	78
Table 3. 1 Oxide composition of Portland cement used in the mixes	93
Table 3. 2 Concrete mix proportions	93
Table 3. 3 Comparison of mechanical properties between low-alkali.....	99
Table 3. 4 Modulus of elasticity of 90-day non-reactive cylinders	106
Table 4. 1 Chemical composition of general-purpose Portland cement (wt.%).....	114
Table 4. 2 Chemical composition of the aggregates (wt. %)	115
Table 4. 3 Mix proportions per cubic metre of concrete.....	127
Table 4. 4 Aggregate reactivity classification (ASTM C1778-20)	141
Table 5. 1 Mix proportions per cubic metre of concrete.....	150
Table 5. 2 Load capacity test results of N5 rebar beams	167
Table 5. 3 Load capacity test results of N8 rebar beams	174
Table 6. 1 ASR acceleration for pull-out test specimens.....	197
Table 6. 2 Average compressive strength, modulus of elasticity and splitting tensile strength at 28-day and after 1, 2 and 3 cycles of autoclaving	201
Table 6. 3 Pull-out test results	202
Table 7. 1 Full-scale 3 m long beams	210
Table 7. 2 Concrete mix proportion for 3 m long full-scale beams.....	212
Table 7. 3 Companion cylinders and prisms of 3 m long full-scale beams	228
Table 7. 4 Modulus of elasticity of cylinders with 1.25% alkali loading	230
Table 7. 5 Compressive strength of cylinders with 1.25% alkali loading	233
Table B. 1 Modulus of elasticity test results	291
Table B. 2 Compressive strength test results	294
Table B. 3 Splitting tensile strength test results	295

Abstract

Alkali-silica reaction (ASR) in concrete is one of the most harmful long-term durability problems for concrete structures. Concerns about the potential risks of ASR to the affected structures led to considerable research in the past several decades. Conventionally, field load testing on actual structures, or large scale in-situ testing are employed to assess the residual load capacity of the ASR affected structures. Such methods, however, are labour intensive, time consuming and may cause unpredictable further damage to the structure. This study aims to investigate the residual load capacity and bond deterioration of ASR affected reinforced concrete structures through laboratory accelerated tests. Based on previous research on accelerated autoclave test for ASR, a novel multi-cycle accelerated test by adopting 80 °C steam warming, with 60-hour cycles and appropriate alkali loading is investigated. Results revealed that, for concrete with highly reactive dacite aggregate and 2.5% alkali boosting, an expansion of 0.18% was achieved after 3 cycles. The compressive strength showed an initial increase at low expansion levels followed by a reduction at higher expansion levels. Modulus of elasticity, however, systematically decreased with increasing expansion. Furthermore, the multi-cycle accelerated test was applied to study the flexural and shear behaviour of small-scale reinforced concrete beams. Results suggest that chemical prestressing induced by ASR expansion has beneficial effects on strength and stiffness of the affected structure at early stages. Effect of high ASR expansion levels on the long-term structural behaviour, however, needs further investigation.